

# SlideRenu®

## PRODUCT DATA SHEET

# SLIDEWAX™

## WATER SLIDE WAX

### DESCRIPTION

SlideWax™ is a nanotechnology polymer wax that has been formulated to bond to fiberglass to protect water slides from the damaging effects of UV rays, harsh weather conditions and environmental contaminants that can fade or discolor water slide surfaces prematurely. SlideWax™ rehydrates surfaces to bring back the deep reflective luster and “LIKE NEW SHINE” to dull looking water slides. The “ULTRA SLICK FINISH” reduces slow spots on the interior riding surface and the deep penetrating wax magnifies the gloss on exterior surfaces to deliver the highest level of protection from the elements unlike any other wax. Significantly outperforms carnauba, car and marine waxes. Depending on rider usage, geographic location and weather conditions, one application typically lasts up to 3 months. One gallon will wax the interior surface of a standard 200 linear foot open flume body slide, roughly 2,000 sq. ft.

### RECOMMENDED USES

SlideWax™ is recommended to be used on interior riding surfaces and may be used on the exterior skin of water slides to protect and enhance appearance. SlideWax™ is a maintenance item which can be used anytime the slide is looking dull, in need of surface protection or to reduce static charge and friction on the ride path.

### DIRECTIONS FOR USE

For SlideWax™ to be effective, the product must be applied to a clean and adequately prepped surface. Any dirt, grease, body-grime, bird droppings, wax and other surface contaminants should be removed first with SlideRenu® SlideDetergent™ (Refer to Product Data Sheet for Application Instructions). After the surface is washed, it should be rinsed with potable quality water through a pressure washer. To remove calcium build-up and hard water mineral deposits, use SlideRenu® Calcitrol™ (Refer to Product Data Sheet for Application Instructions). Rinse the surface with water after

using Calcitrol™ and let dry before applying SlideWax™. Shake well before use and apply SlideWax™ directly onto a dry surface in a swirling motion using a clean, white, dry cloth or SlideRenu® applicator pad. After a light haze appears (about 10 minutes), polish the surface with a buffing machine using a micro-fiber bonnet or by hand using a clean, white, dry cloth. Due to abrasion from riders and constant water flow, two applications are recommended on the rider glide path. When layering SlideWax™, wait 30 minutes before apply the next application.

### PROPERTIES

- APPEARANCE: Light Green Liquid
- ODOR: Mild Sweet Scent
- COVERAGE: 1 Gallon Will Wax the Interior Surface of a 200' Open Body Slide; Approximately 2,000 sq. ft.
- VOC's: None
- PH: Neutral
- SHELF LIFE: 24 Months. Keep From Freezing. Thaw Before Use.
- APPLICATION TEMPERATURE: 50F – 100F.
- FLAMMABLE: No
- BIODEGRADABLE: Yes

### DO NOT MIX THIS PRODUCT WITH ANY OTHER CHEMICALS

### CAUTION: KEEP OUT OF REACH OF CHILDREN

Eye and skin irritant. In case of contact with eyes or skin, flush with water for 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. CONTACT PHYSICIAN IMMEDIATELY.

**This product is available in 1 Gallon bottles and sold exclusively by SlideCare, LLC.**

### SlideCare, LLC

3428 Napa Boulevard Suite 1971 • Avon, Ohio 44011

Tel: 216.503.7203 • Fax: 440.937.8414

[www.sliderenu.com](http://www.sliderenu.com)



Environmentally  
Friendly