

## Water Slide Maintenance Products US Retail Price List

PRODUCT TYPE	PRODUCT NAME	PRODUCT #	PRICE
Scale Removers and Cleaners	Calcitrol™ - Scale Remover	SR33128	\$119.96/gal
	SlideDetergent™ - Heavy Duty Degreaser	SR22128	\$69.96/gal
	SlideSoap™ - Mild Cleaner	SR11128	\$49.96/gal
	SlidePrep™ - Heavy Duty Wax Stripper And Cleaner	SR67128	\$29.96/gal
Compounds, Waxes and Protectants	SlideCompound™ - Oxidation Remover	SR44128	\$119.96/gal
	SlideWax™ - A Nanotechnology Co-Polymer Wax	SR66128	\$159.96/gal
	SlideGloss™ - Sprayable Water Repellent Finishing Wax	SR55128	\$99.96/gal
	SlideArmor™ - Protective Winterizing Sealer	SR77128	\$199.96/gal
	AquaSeal™ - Liquid Water Slide Wax	SR99128	\$139.96/gal
Chlorine-Resistant Coatings	<b>ChloraShield™ CC12</b> - Flexible PolyUrethane Clear Coat	SR70129A SR70129B	\$300.00/1 gal kit
	ChloraShield™ GCS12 - Clear PolyUrethane Gelcoat Sealer	SR76129A SR76129B	\$300.00/1 gal kit
	ColorShield™ UV4 - PolySilox Gelcoat	SR70128A SR70128B	\$300.00/1 gal kit
	Adhesion Base Coat Primer™ - For ColorShield™ UV4	SR88129A SR88129B	\$300.00/1 gal kit
Joint & Fiberglass Repair	SlideCaulk™ - Water-Resistant Seam Sealer	SR291FC	\$21.69/tube
	SlidePutty™ - Polyester Glazing Putty	SR01105	\$59.99/qt
Tower and Stair Maintenance	StairBrite™ - Cleaner/Brightener for Aluminum Stair Treads	SR71128	\$69.99/gal
	StairTape™ - Slip-Resistant Self-Adhesive Safety Tape	SR71060	\$39.99/6 ft
Application Tools	Wool Compounding Pad - For use with SlideCompound™	SR09005	\$18.99/ea
	Foam Finishing Pad - For use with SlideWax™	SR09007	\$18.99/ea
	7 inch Variable Speed Electric Polisher	SR09001	\$89.99/ea
Landing Pads	3' x 5' x 2-1/2" SlidePad®- Landing pad, AquaticBlue Color Blend	SP02535	\$1,000.00/ea
	4' x 6' x 2-1/2" SlidePad®- Landing pad, AquaticBlue Color Blend	SP02546	\$1,400.00/ea
	4' x 8' x 2-1/2" SlidePad®- Landing pad, AquaticBlue Color Blend	SP02548	\$1,900.00/ea
	EdgePad® - Protective Above the Water Edge Landing Pads*	EPCUSTM	Custom Pricing
	SlidePad® Adhesive - Waterproof Bonding Agent	SP3492Q SP3492G	\$42.56/quart \$129.96/gal
	SlidePad® Caulk - Pool Deck And Floor Sealant	SP0001A	\$21.69/tube
Maintenance	Daily Inspection Maintenance Log	SR10000	\$19.99/ea
Disinfectants	Viro-Shield - Pure Hydrogen Peroxide Surface Disinfectant	SR68128	\$29.99/gal

Call our technical representative to discuss your specific maintenance needs or order products online at www.SlideRenu.com

\*EdgePad™ is designed to protect guests from falls occurring on pool edges, play areas, overhead obstructions and pool side walls.

Prices listed do not include shipping costs.

## Slide Repu WAXING PROCEDURE

The following restoration procedure has been developed by AquaShield Products, LLC based on years of experience restoring the LIKE-NEW and WET-LOOK shine to dull color faded water slides and aquatic play structures. To obtain professional results, we recommend a HOT WATER 3,500 PSI pressure washer be used when rinsing the slide.

YOUR SAFETY IS YOUR PERSONAL RESPONSIBILITY. ALWAYS FOLLOW THE APPLICATION INSTRUCTIONS ON THE PRODUCT DATA SHEETS AND SAFETY REQUIREMENTS SHOWN ON THE SDS (Safety Data Sheet) PRIOR TO APPLYING ANY OF OUR PRODUCTS. DO NOT APPLY ANY SLIDERENU® PRODUCTS WHEN THE SURFACE TEMPERATURE IS OVER 100°F.

- 1. If the interior slide joints are not permanently sealed, DO NOT REMOVE any caulk from the interior slide joints. The caulk will be removed and seams re-caulked after the slide has been waxed.
- 2. Clean all surfaces to be restored with undiluted SlideDetergent<sup>TM</sup> using a spray bottle and scrub brush. Refer to the SlideDetergent<sup>TM</sup> label for the proper amount to use, agitation method and work time. Always clean the slide starting from the bottom working your way up to the top of the slide.
- 3. Rinse the slide starting at the top of the slide working your way down to the bottom of the slide with clean tap water through a pressure washer. The negligible amount of SlideDetergent<sup>TM</sup> used WILL NOT CHANGE THE CHEMISTRY OF THE POOL WATER.
- 4. Remove all hard water mineral deposits, water scum lines and calcium scale build-up with undiluted SlideRenu® Calcitrol®. When removing calcium silicate (heavy scale build-up), wet sand with fine 1000-1200 grit sandpaper while spraying undiluted Calcitrol® directly on the surface, while wearing a mask and

safety gloves. Refer to the Calcitrol® label for the proper amount to use, agitation method and work time. The negligible amount of Calcitrol® used WILL NOT CHANGE THE CHEMISTRY OF THE POOL WATER.

- 5. Rinse the slide starting at the top of the slide working your way down to the bottom of the slide with clean tap water through a pressure washer.
- 6. Apply a small amount of SlideCompound $^{\text{TM}}$  to a moistened wool



compounding pad attached to a variable speed buffer or a moistened clean, white cloth to reduce surface friction. Set RPMs at 2000-2500 for heaving cutting and work compound back and forth in a swirling

motion in 2' x 2' sq. ft. sections. Refer to the SlideCompound  $^{\text{\tiny{TM}}}$  label for the proper amount to use, agitation method and work time.

7. Remove SlideCompound™ after a white haze has formed (2-3 minutes) using a clean wool pad at 2500–3000 RPMs. Sweep compound residue to the exit piece of the slide and collect residue in a garbage can, bag or wet/dry vacuum cleaner.

8. Apply a small amount of SlideWax<sup>TM</sup> using a foam finishing pad





attached to a variable speed buffer or a clean white cloth. Set RPMs at 1000-1500 for fine finishing and work wax in a swirling motion in  $2' \times 2'$  ft. sections. Refer to the SlideWax<sup>TM</sup> label for the proper amount to use, agitation method and work time.

- 9. Remove SlideWax™ after a white haze has formed (2-3 minutes) using a clean foam finishing pad at 1500–2000 RPMs. Sweep wax residue to the exit piece of the slide and collect residue in a garbage can, bag or wet/dry vacuum cleaner.
- 10. Remove the existing caulk using a utility knife or hook and pick seal puller. Sand the interior of the seam with 100 grit sandpaper.

  Sweep out the caulk residue and wipe the seam with acetone on a white clean cloth. Caulk the interior joints with SlideCaulk™. Wipe off any excess caulk on the ride path with mineral spirits or acetone.
- 11. After the caulk has formed a film (2-3 hours), spray on/wipe off AquaSeal<sup>TM</sup>, a water repellent and white-haze scale preventative finishing wax. Refer to the AquaSeal<sup>TM</sup> label for the proper amount to use, agitation method and work time. You may use AquaSeal<sup>TM</sup> any time the slide is looking dull or the velocity of the rider has slowed down.
- 12. Use SlideSoap™ as a routine maintenance water slide cleaner to emulsify and prevent excessive build-up of dirt, body-grime, bird droppings, sun tan lotions and most surface contaminants. Using SlideSoap™ throughout the operating season won't strip wax or remove any type of water slide protectant.

DO NOT OPERATE THE SLIDE FOR 6-8 HOURS TO ENSURE THE CAULK AND WAX SYSTEM HAS PROPERLY CURED.

PLEASE NOTE: Severely oxidized slides and slides 10+ years old will generally not hold their WET-LOOK shine for more than two-three (2-3) weeks due to permanent loss of color from chlorinated water, UV exposure and rider abrasion.

## Contact us for a resurfacing quote for your slides!

SlideRenu® has developed the only WATER SLIDE RESTORATION SYSTEM in the aquatics industry that consists of a comprehensive line of specially formulated cleaners, de-scalers, waxes, caulks and PolySilox resurfacing gelcoats and application methods that keep water slides, aquatic play features and soft foam kiddie slides looking LIKE NEW from opening day to closing day!

Using the our system will enhance the SLIP-n-SHINE™ and assist in the prevention of white haze scale build-up when used in a pre-determined maintenance program. To learn more about the products and services we offer, visit www.SlideRenu.com













SlideRenu® products shown above {left to right}: SlideSoap™, SlideDetergent™, Calcitro(®, SlideCompound™, SlideWax™, AquaSeal™, SlideGloss™, SlideCaulk™, Wool and Foam Compounding Pads.

